


VICOM Since 1995		FUJIAM (ODM/OEM)	
Model:8310		Product feature:	
		◆ Easy installation, plug and play	
		◆ View the video anytime and anywhere; support multiple platforms, terminals and networks	
		◆ Clear and smooth video, intelligent transmission	
		◆ Bank level security control and ensure privacy	
		◆ Online firmware upgrade, update function and experience synchronously	
		◆ Smart H.264 video compression algorithm, with lower video bit rates and saving more space when recording	
		◆ Support two-talk Audio,Communicate clearer	
		◆ Support Android/iOS system mobile device, remote real-time monitoring	
		◆ Motion detection, linkage snapshot/video recording, real-time App push notifications	
		◆ Infrared night vision lighting (IR distance: 30 meters), 24 hours day and night monitoring, IR-CUT switch	
		◆ Lighting with white light (Max IR distance:10 meters) 、full color and clear video with little light	
		◆ Support micro SD card (max 128 GB) storage, cloud box and cloud storage	
		◆ Support AI features (Optional): Smart tracking, Face /Sound detection, supprot to be viewd by Alex	
		◆ Support 8-fold digital zoom	
		◆ Support 2. 4G WIFI (IEEE802. 11b/g/n)	
		◆ IP66 grade waterproof	
Specification		2MP	
Main Processor	Chip	ARM	
Image Sensor	Image sensor	1/2.9"color CMOS sensor	
	Lens	f: 2.8mm, 200万 F/No.1.6	
	Visual angle(16:9)	H:105°; V:56°; D:125°	
	Minimum illumination	0.01Lux	
Audio	Input/output	Built-in speaker (8Ω/1W) and microphone (-36dB), support two-way audio	
	Audio compression	AAC	
Video	Video compression	H. 264	
	Lighting frequency	50Hz,60Hz	
	Image frame rate	Max 30fps	
	Display resolution	1920*1080	
	Image adjustment	Brightness, Contrast, Saturation, Sharpness adjustable	
	White balance, BLC	Automatically	
	Night vision	2 dot matrix infrared lamps (850nm), IR distance: 10 meters (optional 2 dot matrix infrared lamps (940nm), IR distance: 5 meters)	
2 dot matrix white light lamps (4000K-5000K), IR distance: 10 meters			
Network	Wireless networks	2. 4G WIFI (IEEE802. 11b/g/n), Built in PCB Board 2DB antenna	
	Ethernet	/	
	Protocols	/	
	IP address	/	
Cloud Plat	Cloud Plat	/	
Alarm	Alarm detection	Motion detection	
	Alarm linkage	Snapshot, audio/video record	
	Alarm notification	Real-time App push notifications	
Intelligence	Power	alexa, Face detection, Sound detection	
Interface	Buttons	DC 5V/1. 2A Micro USB Interface (Europen, UK, USA type for option) power consumption < 8W	
	Ethernet interface	A reset button	
	Ethernet interface	/	
Others	LED instructions	/	
	IP Level	IP65	
	Video Storage	Micro SD card (max 128GB) local storage, cloud box and cloud storage	
Enviornment	Work temperature	-10° ~ 55°C (14°F ~ 131°F)	
	Work humidity	10% ~ 80% (no condensation)	
	Storage temperature	-10°C ~ 60° (14°F ~ 140°F)	
	Storage humidity	0% ~ 90%(no condensation)	
Color	Device color	white plastic texturing, black plastic texture mask	
Specification	Size (LxWxH)	58(L)X42(W)x80(H)mm	
	Weight	—	
Certificate	Certificate	• RoHS, CE, FCC, NCC	
云摄像机——让你我更接近 Cloud IP cameras let us be more closer			