


# KR500 Series



KR500-E/M



KR501-E/M



KR502-E/M



KR503-E/M

## RFID S50/S70 IC Card (13.56 MHz) Readers

### Read Range

KRxxx-E: Up to 10CM

KRxxx-M: Up to 5CM

### Reading Time

≤200ms

### Input Port

External LED Control

External Buzzer Control

### Output Format

KRxxx-E: 26bit Wiegand (Default)

KRxxx-M: 34bit Wiegand (Default)

### Power/Current

DC 6-14V / Max.70mA

### LED

Red and Green LEDs

### Operating Temperature

-20°C to 65°C(-10° to +70°C)

### Material

ABS+PC with texture

### Operating Humidity

10% to 90% relative humidity

non-condensing

### Beeper

Yes

### Index of Protection

KR500-E/M: IP65

KR501-E/M: IP65

KR502-E/M: IP64

KR503-E/M: IP65

## Dimensions

	KR500 E/M	KR501 E/M	KR502 E/M	KR503 E/M
<b>Height:</b>	7.8cm	8.6cm	7.8cm	11.6cm
<b>Depth:</b>	1.6cm	1.6cm	2.6cm	1.6cm
<b>Width:</b>	4.4cm	8.6cm	4.4cm	7.5cm
<b>Weight:</b>	50g	110g	150g	120g

