

# 64 CH NVR

## 12MP/8MP/6MP/5MP/4MP/3MP/1080P/960P/720P HD NVR





VTD-3364B8 supports 64 CH 12MP /8MP / 6MP /5MP / 4MP / 3MP / 1080P /1280 x 1024 / 960P / 720P high definition IP input, which adopts the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system. VTD-3364B8 supports 64 CH IP input, simultaneous 16 CH playback, and 4K high definition display. The product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.

🖉 CE F©

# VICOM

## VTD-3364B8

### 12MP/8MP/6MP/5MP/4MP/ 3MP/1080P/960P/720P HD NVR

#### SPECIFICATIONS

System		
	OS	Embedded Linux
	Network Input	64 CH IPC input
	Incoming Bandwidth	320Mbps
	Outgoing Bandwidth	320Mbps
Video	Network Input Resolution	12MP/ 8MP/ 6MP/5MP/4MP/3MP/1080P/1280×1024/960P/ 720P/960H/D1/CIF
	Output	HDMI 1 : 3840 × 2160@60fps / 3840 × 2160@30fps / 1920 × 1080 /1280×1024 / 1024 × 768 HDMI 2: 1920 × 1080/ 1280×1024 / 1024 × 768 VGA × 1: 1920 × 1080 / 1280×1024 / 1024 × 768
	Compression	H.265S/H.265+/H.265/H.264
1	Multi-screen display	1/4/6/8/9/13/16/25/32/36/64
	Network Input	64 CH IPC audio input
Audio	2-way Audio	$RCA \times 1$
	Local Output	$RCA \times 1$
	Compression	G. 711 (U/A)
	Record Stream	Dual stream recording
Record	Resolution	12MP@20fps; 8MP/ 6MP/5MP/4MP/3MP/1080P/1280×1024/ 960P/ 720P/960H/D1/CIF@30fps(NTSC)/25fps(PAL)
	Mode	Manual/timed/motion/sensor/POS/AI recording
	Simultaneous Playback	Max 16 CH
Dlauhaalt	Search	Time slice / time / event / tag / smart search
Playback	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Decoding Capability	Live View/ Playback	1CH 12MP / 4 CH 5MP / 9 CH 720P/ 16CH 720P
	Mode	Manual, sensor, motion, exception, smart events
Alarm	Input	8 CH local alarm input; supports IPC alarm input
Alalin	Output	4 CH
	Triggering	Record, snapshot, buzzer, preset, e-mail, etc.
Video Structure Analysis	Human/Vehicle Classification	Yes
Other	Fisheye	Supports fisheye dewarping via Web Client and mobile APP
Functions	Plate Recognition	Yes
	Interface	RJ 45 10 / 100 / 1000 Mbps $\times$ 2
Network	Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPs, 802.1x, ONVIF, etc.
	Client Connection	Max.20 users access
Mobile Device	OS	iOS, Andriod
	HDD Interface	SATA $\times$ 8, up to 8TB per HDD; E-SATA $\times$ 2
Storage	RAID	RAID0, RAID1, RAID5, RAID6, RAID10
Rooleum	Local Backup	U disk, USB mobile HDD
Backup 1	Network Backup	Yes
	USB	USB2.0 $\times$ 2, USB3.0 $\times$ 1
Port	RS 485	Yes (full-duplex) ; connectors for PTZ and keyboard
	Remote Controller	Yes

Others	Power Supply	ATX 250W
	Consumption	$\leq$ 30W ( without HDD )
	Dimensions (mm)	445 $\times$ 436 $\times$ 90 (W $\times$ D $\times$ H)
	Working Environment	-10 $\sim$ 50 °C, 10% $\sim$ 90% humidity
	Certificate	CE, FCC, UL
	Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE


#### FEATURES

- Supports 64 CH 12MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 1280×1024/ 960P / 720P / 960H / D1 / CIF IP input
- H.265S/H.265+/H.265/H.254 high profile compression
- Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor/ POS / AI recording
- Playback : 16 CH simultaneous playback
- Search : time slice, time, event, tag search and smart search
- Supports multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- Supports POS information overlay on live view and playback
- Supports RAID0, RAID1, RAID5, RAID6, RAID10
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Multi-
- user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Supports PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Supports NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS



## VTD-3364B8

DIMENSIONS



### **REAR PANEL**

